

RTCU AX9i pro

Advanced Telemetry Appliance

The perfect balance of quality, performance, flexibility and affordability

For Professional M2M Applications

The RTCU AX9i pro has been designed for the most demanding M2M and Internet of Things applications, which cannot be solved with simpler non-programmable devices.

The RTCU AX9i pro rests on the **RTCU M2M Platform**, that brings all the necessary tools together to develop, implement and maintain today's sophisticated M2M/IoT applications.

The **development task** is supported by the **free** RTCU IDE development environment complemented by a large and comprehensive documentation and application example library.

The RTCU Gateway 2 is the corner-stone of the **communication infrastructure** ensuring reliable two-way device communication in any network environment.

Deploying and maintaining new application and firmware versions for devices in the field are handled by the powerful RTCU Deployment Server.

15 years of experience and know-how in one product!

Experience and Know-how

For 15 years Logic IO has been committed to offer the most sophisticated platform for advanced and highly demanding M2M / IoT applications.

The RTCU AX9i pro is the result of this accumulated experience combined with valuable feedback from hundreds of professional and mission critical applications by major organizations around the world.

RTCU products are deployed **underground, stationary, on the road, at sea, on the rail and in the skies!** - In any imaginable application and environment.



Device Advantages

- Quad-band GSM engine.
- Internal/external antenna.
- Digital and analog inputs.
- AC/DC relay outputs.
- Multiple RS232/RS485 channels.
- MODBUS expandable I/O.
- 1-Wire bus.
- ISM medium range RF.
- Digitized voice playback.
- DTMF decoding/transmission.
- Large flash memory capacity.
- Micro SD-CARD with up to 32 GB.
- FAT32 file-system.
- AC / DC powered.
- High-capacity battery.

Platform Advantages

- X32 execution architecture.
- Free RTCU IDE development tool.
- Programmable in VPL.
- Huge standard API.
- Comprehensive protocol support.
- Full featured Device Simulator.
- Sophisticated deployment tools.
- Fast and free email support.
- Backward and forward compatible.

World Leader in Advanced and Professional M2M/IoT Technology since 1999.

RTCU AX9i pro Highlights

Advanced Telemetry Appliance

The RTCU AX9i pro is targeting a broad range of advanced telemetry applications and has been designed according to the highest technical standards for professional industrial use.

- Based on the **RTCU M2M Platform**.
- **X32 execution architecture.**
 - RTCU IDE development tool with full featured device simulator.
 - Huge standard API with more than 800+ functions.
 - Comprehensive protocol support, including: TCP-UDP/IP, FTP, SMTP, RACP, MQTT, MODBUS, FMS/J1939.
- World-wide **Quad-band GSM engine**.
- **Internal and external antenna** connector. Selectable from application.
- Medium range ISM band RF transceiver with on-board antenna.
- Internal SIM-card reader.
- **Digitized audio** can be played over GSM.
- **DTMF** support for implementation of Interactive Voice Response applications.
- Large data-flash/logger memory with a capacity of **4.5 MB**.
- Internal **4 MB FAT32 flash drive**.
- Standard FAT32 **Micro SD-CARD** reader with up to 32 GB capacity.
- **2 x RS232** channels and **2 x RS485** channel.
- **4 x analog inputs** with 0..10 volt / 0..20 mA with **12 bit precision**.
- **4 x analog outputs** with 0..10 volt / 0..20 mA.
- **5 x digital inputs** and **4 x high-power relays**.
- Up to 4 digital inputs can be configured as IEC62053-31 Class A compliant.
- **Expandable I/O** with standard MODBUS modules.
- **1-Wire bus** for accessories such as ID-button reader, temperature sensors, etc.
- Wide AC/DC power operating range from **85..265VAC / 8..36 VDC**.
- On-board **high-capacity Li-Ion battery**.
- Advanced **power-management** with wake-up on a wide range of events.
- High-speed **USB programming** connector.
- Housed in an **ruggedized plastic** encapsulation with **cable glands**.
- **IP65** water protected for outdoor usage.
- Fully supported by the **RTCU Gateway 2** and the **RTCU Deployment Server**.
- **Accessories:** Wi-Fi, Ethernet, Bluetooth and MDT-200 terminal.



Services Available

Technical Support.
Application development support.
Maintenance.
Hardware support.
Warranty services.

Accessories

MDT-200 Data Terminal.
MODBUS IO extension modules.
RF accessories.
Ethernet / Wi-Fi.
Bluetooth.
Antennas.
Cable parts.
1-Wire parts.
Industrial SD-CARD.
...and more.



Find out more and start developing today!

Learn more about the RTCU M2M platform and the X32 architecture in the "The RTCU M2M Platform" data sheet.

To learn more about the technical details and usage of the RTCU AX9i pro, please download the "RTCU AX9i pro Technical Manual".

Also make sure to get the **FREE RTCU IDE** Development Environment, **RTCU Gateway 2** and the **Deployment Server** to get a hands-on experience how rapid development/deployment of game changing M2M/IoT applications were meant to be.

Please visit www.logicio.com

RTCU AX9i pro Specifications

Processor and Main-memory

- Powerful 32-bit ST ARM7 processor.
- 1088 KB fast execution RAM.
- 2304 KB Flash for firmware/application.

Storage

- 3.5 MB persistent data flash.
- 4 MB internal FAT32 flash drive.
- 1 MB circular automatic datalogger.
- 8 KB FRAM with fast access / unlimited write endurance.
- Micro SD-CARD reader. Up to 32 GB.

GSM

- Quad-band GSM engine. 850/900/1800/1900 MHz.
- GPRS Class B, Multislot 10.
- CSD with up to 19 Kbps.
- SMS / PDU.
- DTMF decoding / transmission.
- Digitized voice playback / IVR.
- Micro-SIM 1.8/3 volt.
- Internal SIM card-reader.
- Internal quad-band GSM antenna.
- External or internal antenna selectable by DIP-switch or user application.
- Optional Gemalto SIM-on-chip.

User Interaction

- Three bi-colour LED.
- Yellow status LED.
- DIP-switches.
- Reset/recovery switch.
- Antenna selection dip-switch.
- Configuration jumpers.
- USB-B for service port.

Electrical Specification.

- Supply operating range: 8 to 36 VDC. 85 to 265 VAC.
- Short and reverse power protected.

Battery and Charger

- On-board 2Ah (nominal) Li-Ion battery.
- Intelligent charger with temperature throttle and sub-zero degrees support.
- On-board temperature sensor.

Digital/Analog Interface

- 4 x relay output. Max. 5A @ 250VAC / 30 VDC
- 5 x digital inputs. Logic high: 6 to 40 VDC. Logic low: -5 to 3 VDC.
- 4 x IEC62053-31 Class A input.
- Digital input #5 can be used as ignition.
- 4 x analog inputs. Range is 0..10VDC or 0..20 mA Resolution: 12 bit Precision: $\pm 1.5\%$ FSR @ 25°C
- 4 x analog outputs. Range is 0..10VDC or 0..20 mA Resolution: 10 bit Precision: $\pm 1.5\%$ FSR @ 25°C
- Protected against transients and low-pass filtered.
- Expandable I/O with MODBUS.

Communication

- 1 x RS232 with control signals.
- 1 x RS485.
- 1 x shared RS232 / RS485.
- 1-Wire bus.
- On-board 868 Mhz ISM RF Up to 15 meter indoor / Up to 50 meter outdoor.
- ISM RF can be disabled for world-wide compliance requirements.

Power Management

- 5 execution speeds.
- Wait for Event: Timer, Digital input, RS232, GSM, power change state.
- Wait for event, from: 600 uA@12V.
- Supervision of supply voltage / type.

Internal Interfaces.

- Screw-terminals for: Power, I/O and 12/24V DCOUT.
- Angled screw-terminals for: RS232, RS485, 1-Wire and 3.3V DCOUT.

External Interfaces.

- SMA Female connector for external GSM antenna.
- 3 x PG11 cable glands.
- 2 x PG9 blind plugs.

Physical Characteristics

- Encapsulation: Durable Polycarbonate plastic.
- Approx. 680 gram without accessories.
- W 130 x H 180 x D 60 mm. (without SMA and PG connectors).

Environmental Specification

- Operating temperature: -30 to 60°C.
- Battery charge temperature: -10 to 45 °C
- Recommended storage temperature: 0 to 45°C.
- Humidity: 5..90% (non condensing).
- Ingress Protection: IP65.

Approvals

- CE. EU EMC directive 2004/108/EU.
- Applied R&TTE directive.
- GSM engine: CE/GCF/FCC/PTCRB.

Warranty

- Two-years return to factory parts and labor.
- Optional warranty up to 5 years. (restrictions apply).

Logic IO Worldwide Headquarters

Holmboes Allé 14
8700 Horsens
Denmark
Phone: +45 7625 0210
Fax: +45 7625 0211
Commercial enquiries: sales@logicio.com
Technical support: support@logicio.com
www.logicio.com

Models Available

SKU: RT-AX9IP